

AGENCY LISTING AND APPROVAL

- UL Listed
- FM Approved

TECHNICAL SPECIFICATIONS

SPECIFICATIONS

Physical	4.5" H x 4"W x 1.25" D
Shipping Weight	6.3oz (196g)

ELECTRICAL RATINGS

Operating Voltage:	15 to 32VDC
External Power Supply	Alarm Current: 90mA per module , Standby Current: 13mA @ 24 VDC (nominal)
Max Current	5.1 mA (LED ON)
End-of-Line Resistance:	3.9k ohm
SLC Loop Impedance:	25 ohm
Initiating Device Circuit Wiring Resistance:	25W max

ORDERING INFORMATION

SK-ZONE.	Addressable two-wire interface module
----------	---------------------------------------

ACCESSORIES

SMB500	4" Square surface mount electrical box
--------	--

ENVIRONMENTAL

Operating Temperature:	32°-120°F (0°C – 49°C)
Humidity:	10 to 93% non-condensing)

For a complete listing of all compliance approvals and certifications, please visit <https://buildings.honeywell.com>. Silent Knight™ is a trademark of Honeywell International, Inc. This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice. For Technical Support, please call 0008000502167.

Honeywell International India Pvt Ltd Sector
36, Pace City II, Gurgaon, Haryana India
<https://www.honeywellbuildings.in/>