

TS-7, TS-9

Request to Exit Station

The single gang TS-7 and narrow stile TS-9 request to exit stations with rectangular push button, provide a convenient way to add authorized access control for a variety of applications. TS-7 and TS-9 are available with timer relay for applications that require door to remain unlocked for a specified time.



TS-7



TS-9

Features

Standard Features

- **TS-7** switch mounted on single gang wall plate with 430 stainless steel finish
- **TS-9** switch mounted on narrow 1-3/4" wall plate with 302 stainless steel finish
- 5/8" x 7/8" green rectangular push button; illuminated with hi-brightness LED
- Button labeled "PUSH TO EXIT" for easy to follow egress instructions
- Momentary DPDT action switch

Options

- **TS-7L, TS-9L** with latching action switch
- **TS-7T, TS-9T** with timed output
 - Timer is adjustable 2 to 45 seconds
- Finishes: multiple plate options available
- Custom legends available as custom part

Specifications

Certifications & Listings

- UL 294 listed

Electrical

- DPDT timed contacts, rated 3A at 35 VDC or 120 VAC
- Timed output is SPDT contacts rated 2A at 35VDC
- Switch depth behind plate: 1-1/4"
- Switch terminated with 10" colored leads
- LED operates on 12 or 24 VAC/VDC

Operating Temperature

- -13F to +158 F (-25 to 70 C)